



# Planar PZD2410

## **24" Full HD USB Type-C Docking monitor**

The slim Planar® PZD2410 is a 24" Full HD USB Type-C Docking monitor that provides an easy way to connect and power a PC/laptop. A single USB-C cable can deliver audio, video, data, network connectivity and up to 65 watts of power. The daisy-chain feature simplifies connecting another monitor. It is flicker free and incorporates blue light reduction presets to help lower eye fatigue. The ergonomic stand lets it fit nicely in education, home, office or healthcare applications.



Specification:

Detail:

---

**Product Name**

PZD2410

**Planar Part Number**

998-2945-00

**Viewable Size**

23.8" diagonal (20.75" horizontal x 11.67" vertical)

**Aspect Ratio**

16:9

Specification:

Detail:

**Contrast Ratio (typ)**

1000:1

**Viewing Angle (typ)**

178° Horizontal and Vertical

**Response Time (typ)**

5 ms (GTG)

**Brightness (Typical)**

250 cd/m<sup>2</sup>

**Display Type**

IPS LCD Active Matrix Flat Panel Display (TFT)

**Display Resolution**

Full HD 1080P, 1920 x 1080

**Tilt Range**

-5° to +20°

**Palette**

16.7 million colors

**Pixel Pitch**

0.2745 mm

**Refresh Rate**

48-75Hz (60Hz recommended)

**Dimensions (W x H x D)**

21.2" x 19.6" x 9.0" (539.5 mm x 498.3 mm x 228.9 mm)

**Dimensions without Stand**

21.2" x 12.7" x 2.0" (539.5 mm x 323.1 mm x 50.7 mm)

**Panel Depth**

2.0" (50.7 mm)

**Display Weight**

11.5 lb/5.2 kg (7.5 lb/ 3.4 kg without stand)

**Shipping weight**

15.7 lb (7.1 kg)

**Video Inputs**

USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI®

**Video Outputs**

DisplayPort

Discontinued

Specification:

Detail:

**HDCP**

Yes

**Audio Output**

Integrated 2W/channel stereo speakers, headphone jack

**External Connections**

USB Type C 24-pin, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 2 (Type A) x 3 , RJ45, DisplayPort 20-pin (out)

**USB**

USB-C x 1 (Upstream) (10Gbps), USB3.2 Gen2 x 3 (Downstream with 1 fast charge BC 1.2)

**USB C Power Delivery**

USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A)

**RJ45**

Ethernet LAN (10M/100M/1000M)

**Compatibility**

PC and Mac® (adapter may be required for Mac)

**Power Supply**

Internal

**Power Consumption (max)**

20W typical (<0.5W standby)

**Power Requirements**

AC 100/240 VAC

**Operating Temperature**

0° to +40°C (32° to 104°F)

**Humidity**

10 - 85% RH (non-condensing)

**Mount**

Built-in 100 mm VESA, back

**Product Approvals**

cTUVus, CE , FCC-B, RoHS

**Recommended Usage**

Up to 16 hours per day

Discontinued

Specification:

Detail:

**Service and Support**

3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.

**Options / Features**

IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot

**Blue Light Reduction**

Yes

**Flicker Free**

Yes

**In the Box**

PZD2410 24" LCD Monitor, Power Cord, DP Cable, USB Type-C Cable, User's Guide

**UPC**

8 10689 00988 7

**Recommended Daisy Chain Monitor**

XN2410 (998-94400)

Discontinued

**HDMI®**

Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.