

Planar PZN2710Q

27" Docking Monitor

The Planar® PZN2710Q is a 27" Quad HD USB Type - C Docking monitor with integrated docking station provides a simple and easy way to connect a PC/laptop to the monitor. The monitor enables a single USB Type C cable to deliver audio, video, data, network connectivity, daisy chain, and power delivery up to 65 watts. The Planar PZN2710Q suits nicely into education, home, office or healthcare applications.



Specification:	Detail:
Product Name	PZN2710Q
Planar Part Number	998-2124-00
Viewable Size	27" diagonal (23.53" x 13.21")

Specification: Detail:

Aspect Ratio 16:9

Contrast Ratio (typ) 1000:1

Viewing Angle (typ) 178° Horizontal and Vertical

Response Time (typ) 6 ms (GTG)

Brightness (Typical) 300 cd/m²

Display Type

IPS LCD Active Matrix Flat Panel Display (TFT)

Display Resolution

Display Resolution

Tilt Range -5° to $+20^{\circ}$

Palette 16.7 million colors

Pixel Pitch 0.2331 mm

Refresh Rate 48-75Hz (60Hz recommended)

Dimensions (W x H x

D)

24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm)

Dimensions without

Stand

24.2" x 14.5" x 2.1" (612.84 mm x 367.46 mm x 52.3 mm)

Panel Depth 2.1" (52.3 mm)

Display Weight 13.6 lb/6.16 kg (9.2 lb/ 4.17 kg without stand)

Shipping weight 16.5 lb (7.5 kg)

Video Inputs USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI®

Specification: Detail:

Video Outputs DisplayPort

HDCP Yes

Audio Output Integrated 2W/channel stereo speakers, headphone jack

External USB Type C 24-pin, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out,

Connections USB 3.2 Gen 1 (Type A) x 3, RJ45, DisplayPort 20-pin (out)

USB-C x 1 (Upstream) (5Gbps), USB3.2 Gen1 x 3 (Downstream)

USB C Power USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A)

Delivery

RJ45

Ethe ACLAN (10N/1 OM 10)01) UEC

Compatibility PC and Mac® (adapter may be required for Mac)

Power Supply External (DC power)

Power Consumption

(max)

35W typical (<0.5W standby)

Power Requirements AC 100/240 VAC

Operating 0° to $+40^{\circ}$ C (32° to 104° F)

Temperature

Humidity 10 - 85% RH (non-condensing)

Mount Built-in 100 mm VESA, back

Product Approvals cTUVus, CE , FCC-B, RoHS

Recommended Up to 16 hours per day

Usage

Specification: Detail: 3-Year Customer First ™ Warranty featuring FREE Advance Replacement (US Service and Support only). Please see the warranty document for more details and for replacement procedures outside the US. **Options / Features** IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot **Blue Light Reduction** Yes Flicker Free Yes In the Box PZN2710Q 27" LCD Monitor, Power Cord, HDMI cable, DP Cable, USB Type-C Cable, User's Guide **UPC** 8 10689 00803 3 **Recommended Daisy** PXN2710Q (998-2123-00) **Chain Monitor HDMI®**

Planar utilizes HDMI® standar Is in this product. The terms HD /II, HDMI High-Lafinition Muclime III Interface, HD /IIT accedes and the HL MI Logos are trademarks or registered trademarks of HDML accessing Administrator, Inc.

Copyright © 2025 All rights reserved.